



MARİS ENERJİ TİC.LTD.ŞTİ.

www.marisenerji.com

info@marisenerji.com



Battery Model: 34M

Part Number: 8006-006

Nominal Voltage: 12 volts

NSN: 6140 01 475 9416

Description: High power, sealed lead acid, marine starting battery

Physical Characteristics:

Plate Design: High purity lead-tin alloy. Wound cell configuration utilizing proprietary *SPIRALCELL*® technology.
Electrolyte: Sulfuric acid, H₂SO₄
Case: Polypropylene
Color: Case: Dark Gray
Cover: "OPTIMA" Blue
Group Size: BCI: 34

	Standard	Metric
Length:	10.018"	254.46 mm
Width:	6.829"	173.46 mm
Height:	7.925"	201.30 mm (Height at the top of terminals)
Weight:	38.4 lb	17.4 kg

Terminal Configuration: SAE / BCI automotive and 5/16"-18UNC-2A threaded stainless steel stud.

Performance Data:

Open Circuit Voltage (Fully charged): 12.8 volts
Internal Resistance (Fully charged): .0030 ohms
Capacity: 50 Ah (C/20)
Reserve Capacity: BCI: 100 minutes
(25 amp discharge, 80°F (26.7°C), to 10.5 volts cut-off)

Power:

CCA (BCI 0°F): 800 amps
MCA (BCI 32°F): 1000 amps

Recommended Charging:

The following charging methods are recommended to ensure a long battery life: (Always use a voltage regulated charger with voltage limits set as described below.)

Model: 34M

These batteries are designed for engine starting applications. They are not recommended or warranted for use in deep cycle applications.



MARİS ENERJİ TİC.LTD.ŞTİ.

www.marisenerji.com

info@marisenerji.com

Recommended Charging Information:

Alternator:	13.3 to 15.0 volts
Battery Charger (Constant Voltage):	13.8 to 15.0 volts; 10 amps maximum; 6-12 hours approximate
Float Charge:	13.2 to 13.8 volts; 1 amp maximum; (indefinite time at lower voltages)
Rapid Recharge:	Maximum voltage 15.6 volts. No current limit as long as battery
(Constant voltage charger)	temperature remains below 125°F (51.7°C). Charge until current drops below 1 amp.
All limits must be strictly adhered to.	

Recharge Time: (example assuming 100% discharge – 10.5 volts)

Current	Approximate time to 90% charge
100 amps	35 minutes
50 amps	75 minutes
25 amps	140 minutes

Recharge time will vary according to temperature and charger characteristics. When using Constant Voltage chargers, amperage will taper down as the battery becomes recharged. When amperage drops below 1 amp, the battery will be close to a full state of charge.

(All charge recommendations assume an average room temperature of 77°F (25°C).

Always wear safety glasses when working with batteries.

Always use a voltage regulated battery charger with limits set to the above ratings. Overcharging can cause the safety valves to open and battery gases to escape, causing premature end of life. These gases are flammable! You cannot replace water in sealed batteries that have been overcharged. Any battery that becomes very hot while charging should be disconnected immediately.

Not fully charging a battery can result in poor performance and a reduction in capacity.

Shipping and Transportation Information:

OPTIMA batteries can be shipped by AIR. The battery is nonspillable and is tested according to ICAO Technical Instructions DOC. 9284-AN/905 to meet the requirements of Packing Instructions No. 806 and is classified as non-regulated by IATA Special Provision A-48 and A-67 for UN2800. Terminals must be protected from short circuit.

BCI = Battery Council International

OPTIMA Batteries

Product Specifications: Model 34M

December 2008



MARİS ENERJİ TİC.LTD.ŞTİ.

www.marisenerji.com

info@marisenerji.com



Battery Model: D27M

Part Number: 8027-127

Nominal Voltage: 12 volts

NSN: Number applied for, product currently available

Description: High power, dual purpose engine start and deep cycle, sealed lead acid battery

Physical Characteristics:

Plate Design: High purity lead-tin alloy. Wound cell configuration utilizing proprietary *SPIRALCELL*® technology.

Electrolyte: Sulfuric acid, H₂SO₄

Case: Polypropylene

Color: Case: Light Gray
Cover: "OPTIMA" Blue

Group Size: BCI: 27

	Standard	Metric
Length:	12.160"	308.86 mm
Width:	6.762"	171.75 mm
Height:	8.700"	220.98 mm (Height at the top of terminals)
Weight:	53.8 lb	24.4 kg

Terminal Configuration: SAE / BCI automotive and 5/16"-18UNC-2A threaded stainless steel stud.

Performance Data:

Open Circuit Voltage (Fully charged): 13.1 volts

Internal Resistance (Fully charged): .0025 ohms

Capacity: 66 Ah (C/20)

Reserve Capacity: BCI: 140 minutes
(25 amp discharge, 80°F (26.7°C), to 10.5 volts cut-off)

Power:

CCA (BCI 0°F): 800 amps

MCA (BCI 32°F): 1000 amps

Recommended Charging:

The following charging methods are recommended to ensure a long battery life: (Always use a voltage regulated charger with voltage limits set as described below.)

Model: D27M

These batteries are designed for starting and deep cycle applications and for use in vehicles with large accessory loads.



MARİS ENERJİ TİC.LTD.ŞTİ.

www.marisenerji.com

info@marisenerji.com

Recommended Charging Information:

Alternator:	13.65 to 15.0 volts
Battery Charger (Constant Voltage):	13.8 to 15.0 volts; 10 amps maximum; 6-12 hours approximate
Float Charge:	13.2 to 13.8 volts; 1 amp maximum; (indefinite time at lower voltages)
Rapid Recharge:	Maximum voltage 15.6 volts. No current limit as long as battery temperature remains below 125°F (51.7°C). Charge until current drops below 1 amp.
(Constant voltage charger)	
Cyclic or Series String Applications:	14.7 volts. No current limit as long as battery temperature remains below 125°F (51.7°C). When current falls below 1 amp, finish with 3 amp constant current for 1 hour.
	All limits must be strictly adhered to.

Recharge Time: (example assuming 100% discharge – 10.5 volts)

Current	Approximate time to 90% charge
100 amps	45 minutes
50 amps	98 minutes
25 amps	185 minutes

Recharge time will vary according to temperature and charger characteristics. When using Constant Voltage chargers, amperage will taper down as the battery becomes recharged. When amperage drops below 1 amp, the battery will be close to a full state of charge.

(All charge recommendations assume an average room temperature of 77°F (25°C).

Always wear safety glasses when working with batteries.

Always use a voltage regulated battery charger with limits set to the above ratings. Overcharging can cause the safety valves to open and battery gases to escape, causing premature end of life. These gases are flammable! You cannot replace water in sealed batteries that have been overcharged. Any battery that becomes very hot while charging should be disconnected immediately.

Not fully charging a battery can result in poor performance and a reduction in capacity.

Shipping and Transportation Information:

OPTIMA batteries can be shipped by AIR. The battery is nonspillable and is tested according to ICAO Technical Instructions DOC. 9284-AN/905 to meet the requirements of Packing Instructions No. 806 and is classified as non-regulated by IATA Special Provision A-48 and A-67 for UN2800. Terminals must be protected from short circuit.

BCI = Battery Council International

OPTIMA Batteries

Product Specifications: Model D27M

December 2008

**Battery Model:** D31M**Part Number:** 8052-161**Nominal Voltage:** 12 volts**NSN:** 6140 01 502 4405**Description:** High power, dual purpose engine start and deep cycle, sealed lead acid battery**Physical Characteristics:**

Plate Design:	High purity lead-tin alloy. Wound cell configuration utilizing proprietary <i>SPIRALCELL</i> ® technology.
Electrolyte:	Sulfuric acid, H ₂ SO ₄
Case:	Polypropylene
Color:	Case: Light Gray Cover: "OPTIMA" Blue
Group Size:	BCI: 31

	Standard	Metric
Length:	12.774"	324.46 mm
Width:	6.529"	165.84 mm
Height:	9.370"	238.00 mm (Height at the top of terminals)
Weight:	59.8 lb	27.1 kg

Terminal Configuration: SAE / BCI automotive and 5/16"-18UNC-2A threaded stainless steel stud.

Performance Data:

Open Circuit Voltage (Fully charged):	13.1 volts
Internal Resistance (Fully charged):	.0025 ohms
Capacity:	75 Ah (C/20)
Reserve Capacity:	BCI: 155 minutes (25 amp discharge, 80°F (26.7°C), to 10.5 volts cut-off)

Power:

CCA (BCI 0°F):	900 amps
MCA (BCI 32°F):	1125 amps

Recommended Charging:

The following charging methods are recommended to ensure a long battery life: (Always use a voltage regulated charger with voltage limits set as described below.)

Model: D31M

These batteries are designed for starting and deep cycle applications and for use in vehicles with large accessory loads.



MARİS ENERJİ TİC.LTD.ŞTİ.

www.marisenerji.com
info@marisenerji.com

Recommended Charging Information:

Alternator:	13.65 to 15.0 volts
Battery Charger (Constant Voltage):	13.8 to 15.0 volts; 10 amps maximum; 6-12 hours approximate
Float Charge:	13.2 to 13.8 volts; 1 amp maximum; (indefinite time at lower voltages)
Rapid Recharge:	Maximum voltage 15.6 volts. No current limit as long as battery
(Constant voltage charger)	temperature remains below 125°F (51.7°C). Charge until current drops below 1 amp.
Cyclic or Series String Applications:	14.7 volts. No current limit as long as battery temperature remains below 125°F (51.7°C). When current falls below 1 amp, finish with 3 amp constant current for 1 hour.
All limits must be strictly adhered to.	

Recharge Time: (example assuming 100% discharge – 10.5 volts)

Current	Approximate time to 90% charge
100 amps	52 minutes
50 amps	112 minutes
25 amps	210 minutes

Recharge time will vary according to temperature and charger characteristics. When using Constant Voltage chargers, amperage will taper down as the battery becomes recharged. When amperage drops below 1 amp, the battery will be close to a full state of charge.

(All charge recommendations assume an average room temperature of 77°F (25°C).

Always wear safety glasses when working with batteries.

Always use a voltage regulated battery charger with limits set to the above ratings. Overcharging can cause the safety valves to open and battery gases to escape, causing premature end of life. These gases are flammable! You cannot replace water in sealed batteries that have been overcharged. Any battery that becomes very hot while charging should be disconnected immediately.

Not fully charging a battery can result in poor performance and a reduction in capacity.

Shipping and Transportation Information:

OPTIMA batteries can be shipped by AIR. The battery is nonspillable and is tested according to ICAO Technical Instructions DOC. 9284-AN/905 to meet the requirements of Packing Instructions No. 806 and is classified as non-regulated by IATA Special Provision A-48 and A-67 for UN2800. Terminals must be protected from short circuit.

BCI = Battery Council International

OPTIMA Batteries
Product Specifications: Model D31M
December 2008

**Battery Model:** D34M**Part Number:** 8016-103**Nominal Voltage:** 12 volts**NSN:** 6140 01 475 9355**Description:** High power, dual purpose engine start and deep cycle, sealed lead acid battery**Physical Characteristics:****Plate Design:** High purity lead-tin alloy. Wound cell configuration utilizing proprietary *SPIRALCELL*® technology.**Electrolyte:** Sulfuric acid, H₂SO₄**Case:** Polypropylene**Color:** Case: Light Gray
Cover: "OPTIMA" Blue**Group Size:** BCI: 34

	Standard	Metric
Length:	10.018"	254.46 mm
Width:	6.829"	173.46 mm
Height:	7.925"	201.30 mm (Height at the top of terminals)
Weight:	43.5 lb	19.7 kg

Terminal Configuration: SAE / BCI automotive and 5/16"-18UNC-2A threaded stainless steel stud.

Performance Data:**Open Circuit Voltage (Fully charged):** 13.1 volts**Internal Resistance (Fully charged):** .0028 ohms**Capacity:** 55 Ah (C/20)**Reserve Capacity:** BCI: 120 minutes
(25 amp discharge, 80°F (26.7°C), to 10.5 volts cut-off)**Power:****CCA (BCI 0°F):** 750 amps**MCA (BCI 32°F):** 870 amps**Recommended Charging:**

The following charging methods are recommended to ensure a long battery life: (Always use a voltage regulated charger with voltage limits set as described below.)

Model: D34M

These batteries are designed for starting and deep cycle applications and for use in vehicles with large accessory loads.

**Recommended Charging Information:**

Alternator:	13.65 to 15.0 volts
Battery Charger (Constant Voltage):	13.8 to 15.0 volts; 10 amps maximum; 6-12 hours approximate
Float Charge:	13.2 to 13.8 volts; 1 amp maximum; (indefinite time at lower voltages)
Rapid Recharge:	Maximum voltage 15.6 volts. No current limit as long as battery temperature remains below 125°F (51.7°C). Charge until current drops below 1 amp.
(Constant voltage charger)	
Cyclic or Series String Applications:	14.7 volts. No current limit as long as battery temperature remains below 125°F (51.7°C). When current falls below 1 amp, finish with 2 amp constant current for 1 hour.
	All limits must be strictly adhered to.

Recharge Time: (example assuming 100% discharge – 10.5 volts)

Current	Approximate time to 90% charge
100 amps	35 minutes
50 amps	75 minutes
25 amps	140 minutes

Recharge time will vary according to temperature and charger characteristics. When using Constant Voltage chargers, amperage will taper down as the battery becomes recharged. When amperage drops below 1 amp, the battery will be close to a full state of charge.

(All charge recommendations assume an average room temperature of 77°F (25°C).

Always wear safety glasses when working with batteries.

Always use a voltage regulated battery charger with limits set to the above ratings. Overcharging can cause the safety valves to open and battery gases to escape, causing premature end of life. These gases are flammable! You cannot replace water in sealed batteries that have been overcharged. Any battery that becomes very hot while charging should be disconnected immediately.

Not fully charging a battery can result in poor performance and a reduction in capacity.

Shipping and Transportation Information:

OPTIMA batteries can be shipped by AIR. The battery is nonspillable and is tested according to ICAO Technical Instructions DOC. 9284-AN/905 to meet the requirements of Packing Instructions No. 806 and is classified as non-regulated by IATA Special Provision A-48 and A-67 for UN2800. Terminals must be protected from short circuit.

BCI = Battery Council International

OPTIMA Batteries Product Specifications: Model D34M
December 2008